



This is a digital copy of a book that was preserved for generations on library shelves before it was carefully scanned by Google as part of a project to make the world's books discoverable online.

It has survived long enough for the copyright to expire and the book to enter the public domain. A public domain book is one that was never subject to copyright or whose legal copyright term has expired. Whether a book is in the public domain may vary country to country. Public domain books are our gateways to the past, representing a wealth of history, culture and knowledge that's often difficult to discover.

Marks, notations and other marginalia present in the original volume will appear in this file - a reminder of this book's long journey from the publisher to a library and finally to you.

### Usage guidelines

Google is proud to partner with libraries to digitize public domain materials and make them widely accessible. Public domain books belong to the public and we are merely their custodians. Nevertheless, this work is expensive, so in order to keep providing this resource, we have taken steps to prevent abuse by commercial parties, including placing technical restrictions on automated querying.

We also ask that you:

- + *Make non-commercial use of the files* We designed Google Book Search for use by individuals, and we request that you use these files for personal, non-commercial purposes.
- + *Refrain from automated querying* Do not send automated queries of any sort to Google's system: If you are conducting research on machine translation, optical character recognition or other areas where access to a large amount of text is helpful, please contact us. We encourage the use of public domain materials for these purposes and may be able to help.
- + *Maintain attribution* The Google "watermark" you see on each file is essential for informing people about this project and helping them find additional materials through Google Book Search. Please do not remove it.
- + *Keep it legal* Whatever your use, remember that you are responsible for ensuring that what you are doing is legal. Do not assume that just because we believe a book is in the public domain for users in the United States, that the work is also in the public domain for users in other countries. Whether a book is still in copyright varies from country to country, and we can't offer guidance on whether any specific use of any specific book is allowed. Please do not assume that a book's appearance in Google Book Search means it can be used in any manner anywhere in the world. Copyright infringement liability can be quite severe.

### About Google Book Search

Google's mission is to organize the world's information and to make it universally accessible and useful. Google Book Search helps readers discover the world's books while helping authors and publishers reach new audiences. You can search through the full text of this book on the web at <http://books.google.com/>

0 2476 3142 0

4.1567-3

TRANSFERRED TO  
FINE ARTS LIBRARY



Harvard College Library

FROM

*School of Engineering*

*Transferred to Harvard College Library*

















FRONTISPIECE.

Smith's  
*Modelling*  
In Paper.

T. A. RICHARDSON,

Author.


LONDON:  
JOHN WEALE.



The Art  
— of —  
Architectural  
Modelling  
In Paper.

BY  
T. A. RICHARDSON,  
ARCHITECT.

LONDON :  
JOHN WEALE.






Page 100

The Art  
— of —  
Architectural  
Modelling  
In Paper.

BY  
T. A. RICHARDSON,  
ARCHITECT.

LONDON :  
JOHN WEALE.





2

THE ART  
OF  
ARCHITECTURAL MODELLING  
IN PAPER.

BY  
T. A. RICHARDSON,  
ARCHITECT.

WITH ILLUSTRATIONS DESIGNED BY THE AUTHOR,  
AND ENGRAVED BY O. JEWITT.

LONDON:  
JOHN WEALE, 59, HIGH HOLBORN.  
1859.



FA 1567.3

HARVARD UNIVERSITY  
SCHOOL OF ENGINEERING

JUN 20 1917  
TRANSFERRED TO  
HARVARD COLLEGE LIBRARY

LONDON :  
BRADBURY AND EVANS, PRINTERS, WHITEFRIARS.

## PREFACE.



IN offering the following practical dissertation (the first ever yet published) upon the Art of Architectural Modelling, the Author feels that he is supplying a want that must have been long felt by many students and others in the architectural profession. The utility of the "Model," coupled with its beauty, is ample recommendation of the study; and the modeller will be able to furnish the architect with sure and certain means that he may find weighty difficulties surmounted, especially in the case of uncomprehending clients, by giving to them the designs of their edifices

with a distinctness almost equal to the real work when completed. With many clients, even "perspectives" are poorly understood, which seldom fails to cause some slight dissatisfaction on their part when they see too late certain things that the eye would have detected in the model and corrected in the outset. Models are becoming very general, where buildings are subjects of competition; and as this course of procedure and honourable encounter bids fair (when weeded of some of its present objections) to open up a good and honourable system, whereby the "*race may be to the swift*," the importance of the following brief and simple Treatise on the subject, becomes doubly clear.

T. A. R.

CHESTER, *March*, 1859.

# CONTENTS.

---

	PAGE
PREFACE . . . . .	iii
INTRODUCTION . . . . .	13

## PART I.

### OF THE MATERIALS REQUIRED.

PAPER . . . . .	19
ADHESIVE MATERIAL . . . . .	21
OTHER REQUISITES . . . . .	22

## PART II.

### OF THE INSTRUMENTS NECESSARY.

CUTTING BOARD . . . . .	24
MODELLING PRESS . . . . .	25
T SQUARE . . . . .	29
ADJUSTING STRAIGHT EDGE . . . . .	31
CUTTING KNIVES . . . . .	33
ADJUSTING KNIFE COMPASS . . . . .	36

## PART III.

## THE COMMENCEMENT AND FINISH OF A MODEL.

	PAGE
OUTLINE PLAN . . . . .	40
THICKNESS OF PAPER FOR WALLS . . . . .	40
OUTLINING THE ELEVATION . . . . .	41
WINDOW FRAMES . . . . .	44
GROUND PLAN, OUTLINE PLAN . . . . .	45
GLASS OR OTHER BACKING TO WINDOWS . . . . .	48
DOORS . . . . .	49, 51
FORMING MITRES . . . . .	52
INCIDENTAL PRESSURE DURING PROGRESS . . . . .	54
FIXING THE MODEL TOGETHER . . . . .	54
BLOCKING PIECES TO ANGLES . . . . .	54
PREPARATION FOR FINAL FASTENING TO STAND . . . . .	56
METHOD OF INSERTING THE WOOD STAY . . . . .	57
THE CORNICE . . . . .	59
MOULDING TOOLS . . . . .	60
DETAILS OF WINDOWS . . . . .	61
CIRCULAR PEDIMENTS . . . . .	64
QUOINS . . . . .	64
CIRCULAR ARCHITRAVES . . . . .	65
KEYSTONES . . . . .	65, 66

# CONTENTS.

vii

	PAGE
CANTALIVERS . . . . .	66
CUTTING, CURVES . . . . .	66
PLAIN ARCHITRAVES . . . . .	67
CUTTING IN GENERAL WITH THE KNIFE . . . . .	68
DETAILS OF WINDOWS . . . . .	69
THE GREENHOUSE . . . . .	73, 75
PILASTERS . . . . .	75
CAP AND BASE . . . . .	75
ROOF OF GREENHOUSE . . . . .	76, 77
CORNICE AND PLINTH . . . . .	79
CHIMNEYS . . . . .	79
ROOF OF HOUSE . . . . .	83, 84, 85
REMOVING THE MODEL . . . . .	88
PREPARATION OF FINAL STAND . . . . .	88
PREPARATION OF GLASS SHADE . . . . .	89
FIXING THE MODEL TO ITS STAND . . . . .	89
GOthic ARCHITECTURE, AND REFERENCE TO IN GLOSSARY . . . . .	90

## PART IV.

### HINTS ON LANDSCAPE GARDENING.

INTRODUCTION . . . . .	91
PEDESTALS, SUN DIALS, GATE PIERS, BALLUSTERS . . . . .	93
IMITATIONS OF LAWNS, GRASS, ETC. . . . .	94

	PAGE
WATER, ROCKS, AND GROTTOES . . . . .	94
WALKS, DRIVES, FLOWER BEDS, TREES, AND SHRUBS . . .	95

## PART V.

A GLOSSARY, CONTAINING THE METHOD OF WORKING VARIOUS DETAILS NOT HITHERTO DESCRIBED . . . . .	97
TO THE READER. FINIS. . . . .	111

THE ART  
OF  
ARCHITECTURAL MODELLING  
IN PAPER.

---

INTRODUCTION.

---

THE art of Architectural Modelling is not so difficult to acquire, as an observer, examining a model and admiring the minuteness of its parts, would be led to suppose. But in order to gain a certain degree of proficiency, a large amount of patience and perseverance is absolutely necessary. The great beauties of a model consist,



firstly, in perfect symmetry and correctness of parts, all the angles being clear, well-defined, and sharp, the various minutiae of detail accurately delineated ; and secondly, to the straightness and evenness of the horizontal and perpendicular lines. It will be, therefore, readily understood, that it is these portions of the manipulation which demand the student's attention, more particularly as the joining of the paper or cardboard by means of a mitre, as well as the cutting of lines on the slant in either a horizontal or curved direction, is somewhat difficult. These difficulties which arise in the student's path are, however, easily to be overcome, and he must not grow faint-hearted if, after repeated trials, he does not succeed in producing the required effect. Rather at this juncture let him examine some model by an adept in the art, comparing his work with it. By these means he will be enabled to see the points in his own requiring

improvement, and then let him continue to labour perseveringly and diligently until he gains a perfect command of his knife and materials, and few will be found but will admit that the result at last obtained fully repays him for his time and labour. There is no doubt that the art is of very great antiquity, and that in former times no building of importance was erected without one having been previously constructed. This not only aided the successful carrying out of the architect's drawings, but enabled him and his employer to judge better as to the general effect the work would have when completed.

We have mention made of models as early as 1546, when San Gallo (a pupil of Bramante, the original architect of St. Peter's, at Rome), either himself constructed, or caused to be, a model of his proposed designs for that magnificent structure, in order that the whole might be carried out in the same spirit in the event of

his death. On this latter event occurring, the immortal Michael Angelo Buonarotti undertook the important office of architect to St. Peter's. One of his first tasks was to set aside the model of his predecessor, which had occupied many years in constructing, at a cost of many thousand pounds, while he constructed himself, at a trifling expense and in a few days, another model of his intended work. Numerous other instances of the practical utility of this branch of art might be cited, but the author deems it unnecessary, its importance being at once obvious; and this little work, though devoid of all technicalities, too frequently the fault of works of this description, yet is intended shall be eminently practical. To a large and increasing body, the architectural assistants, it is hoped that this little hand-book will prove to be acceptable; and though written principally for the professional man, it is hoped it may not prove utterly useless or uninteresting

to others, who though not members of the architectural profession may yet possess sufficient taste and skill to wish to perpetuate

## A DESIGN IN PAPER.



## PART I.

### OF THE MATERIALS REQUIRED.



THE materials the architectural modeller will require for his work, are, for the most part, few, simple, and inexpensive. They are also easily procured at any of the Artists' Repositories. It is not, therefore, so much in the material employed, but in the skill displayed in the working, that the beauties of a model consist. The principle in this description of modelling being, that every possible part be constructed of paper, it is necessary that this should be procured of the description best suited to the nature of the work, and of the best possible quality. Inferior papers are hard,

contain knots and other imperfections, and are very frequently gritty; this latter imperfection, by destroying the delicate edge of the knife, prevents the work having that sharp appearance so much to be desired. The paper I use, and have always found the best for all purposes, has a surface similar to that of Whatman's double-elephant drawing paper, and is, I believe, sold under the name of Crayon paper: a specimen is bound with this book, forming the *next page*; it is of a pale cream-colour, bearing a strong semblance in tint to Bath-stone, but I have procured it from this to the shades necessary for the roofs of models. It is firm, though not hard, in texture, and not being too spongy, does not absorb to too great a degree the paste used in fastening together the sheets for the various thicknesses required, thus ensuring their firmness, a matter of the highest importance, otherwise in thin strips

ar

io:

if

a:

I

all

of

and

a







consisting of four, five, or more thicknesses of paper, upon their being cut each would part and defeat the desired end. -

The most useful tint of this paper is the one already described, as it can be easily tinted to represent bricks or rubble, &c., should it be necessary,—for instance, in a building where the quoins, dressings, &c., were in stone, the rest in random rubble or brick, it would enable you to mark them with a HHH pencil, and tint before your work was made up. I have constructed several models in pure white Bristol board, but it is a tedious hard material to work in, though the result is very fine.

The next most important auxiliary is an adhesive material for fastening the sheets together to produce the necessary thicknesses of cardboard, and to fix the whole together and the several parts in their places. For the former a paste of flour made in the following manner,

will be found to be the best. To every two table-spoonfuls of the best wheaten flour, add a tea-spoonful of common moist or brown sugar, and a little corrosive sublimate, the whole to be boiled, and while boiling continually stirred to prevent lumps, till of the right consistency. If a few drops of some essential oil, say lavender or peppermint, be added, the usual mouldiness will not appear, and the paste will keep for a great length of time. For the latter, a gum must be used, prepared by the following proportions. To each six ounces of the best gum arabic, add an ounce or less of moist or lump sugar, one teaspoonful of lavender or other essential oil, and a table-spoonful of gin, the whole to be mixed in *cold* water (no heat being in any way applied) to the consistency of a thick syrup.

Other requisites are sheets of mica or talc, to be procured at the ironmonger's, and used for

windows, sky-lights, &c.; pieces of soft deal or beech wood, to form any small detail such as pinnacles to barge boards, &c., that it may not be advisable or possible to form in paper; wire, lead, cord, velvet, and numerous other nick-nacks, which will occur to the modeller as his work proceeds, and which will hereafter, in their place, be carefully described.

## PART II.

### OF THE INSTRUMENTS NECESSARY.

---

THE first thing the artist must procure must be a board of fine, close-grained wood, free from knots, to prepare and cut the several parts of his work upon. The best for this cutting-board is beech, sycamore, or pear-tree wood; it should be, at the least, one and a-half inch thick, by twelve inches broad, and about eighteen inches in length. I should prefer it even thicker than stated, as continual planing of the surface to erase the marks of the knife soon reduces its thickness. Let it be squared perfectly every way to allow the T square to work accurately along its edge. As before stated, care must be


taken, when the surface has become too much cut up, to have it replaned, or otherwise the knife is apt to follow the marks in the board, and cut the paper irregularly upon the under side. The size of board mentioned will be found most useful for all ordinary purposes; should the work be of very large dimensions, of course another must be procured, proportionally larger. Two or three boards of close-grained deal will also be found of service for cutting obliquely, &c., &c.

#### THE MODELLING PRESS.

This apparatus will be found of essential service to the artist, as by its aid he forms the cardboard which is the basis of his model. It may be either of iron or wood; the former is lighter, and more elegant in appearance, but the latter, though plain and homely, is in my opinion preferable in many respects. A common copying press may be used, care being taken not to place

the damp paper between the iron, but between two hard, close-grained pieces of wood. On page 27 is an illustration of the press I use, which any joiner can construct for a few shillings. It consists of a cross-beam, A, through which the screw passes; two uprights, BB; a bottom, C, to which, and to the cross-beam, the uprights must be firmly mortised. Between them is a moveable top-piece, D, which by means of cord running through two small pulleys, E E, keeps it pressing continually against the screw; the weight F, at the end of the cord being slightly heavier than will balance the top-piece. By these means, as you unwind the screw, either to place under, or look at the progress of work already there, the top-piece moves out of your way. The sizes of the wood for the different portions is given, and care must be observed in not breaking it by too great a pressure of the screw; as the object of the press is to keep

# THE MODELLING PRESS.




## SIZES.

C	Bottom piece . .	18 inches by 12 inches by 2 inches.
B B	Uprights . . . .	12 do. — 4 do. — 1½ do.
A	Cross beam . . .	15 do. — 4 do. — 2½ do.
	The screw .	1½ths inch in diameter.





the sheets flatly and firmly together, while the adhesive material sets, no undue degree of force is necessary; indeed it will, for reasons hereafter to be described, be found a disadvantage to press them too closely.




THE T-SQUARE.

This square is formed like the ordinary drawing-squares, with the exception that the blade A is made of steel; this is firmly screwed to a stock of hard wood, which has on each side of the blade a small piece at c c cut out; the object of this is to allow the knife to cut completely to the edge of the paper. The advantage, in fact, the

necessity for a steel blade, will be obvious ; were it of wood, the pressure of the knife along its edge would indent, or cut it. This square will be found adapted for every description of large and small work, but should the cardboard be of great thickness it is apt to stir, and by so doing cause irregularity of line. To remedy this an instrument is used, called an adjusting straight-edge. A is a straight ruler of flat brass, or of steel, like the blade of the T-square. It is contrived to move to and from the surface of the board upon the upright screws, B B, while a dovetail groove is fitted with a piece of brass to run along it, to allow of the horizontal movement of the ruler. The paper (upon which the cutting-off line has been previously marked) is placed upon the board, the straight-edge adjusted to the line ; the straight-edge being then firmly screwed down upon it by means of the two small thumb-screws, 3 3, it is rendered immoveable during the

progress of the work, this will be better understood from the annexed engraving.




THE ADJUSTING STRAIGHT-EDGE.

No. 1 is a section of the cutting-board, showing the groove in which the piece of brass runs. 2, The brass, to which is attached the thumb-screws, by means of a screw through the eye at B. 3 3 3, Thumb-screws, to screw down the ruler upon the paper. The brass rule should not be less than an eighth of an inch in thickness, otherwise it may bend; if steel it will do a little less.

This instrument will be found particularly useful in cutting the necessary mitres for joining together the edges of the work, or for any other

work of similar description, such as the copings to walls, mouldings of every description, &c., &c. Having now described these very important instruments in a way we hope may prove perfectly intelligible, we proceed to state the requirements in those necessary ones, knives. The number of these the artist will use, is regulated more by his own fancy than anything else; but there are three shapes he will find absolutely necessary. In modelling, as in painting, there are numerous tricks and contrivances for producing various effects; and as the painter will often value a bit of old scrubby, worn-down brush, so the modeller will find various cutting instruments materially assist him, such as the broken blade of a knife, a steel pen, a bradawl, &c., &c., many of these producing effects that more elaborate instruments would have failed doing. On page 33 will be found an engraving representing three requisite varieties of knives. No. 1. This knife is




**MODELLING KNIVES.**



long in the blade, and, as will be found in all the others, is perfectly straight on the cutting edge; this knife is used to cut straight lines in all directions through strong work, cutting oblique lines, mitres, splays, &c. No. 2. One for lighter work used in forming or modelling ornaments, or, in general, cutting work of a lighter and neater character. No. 3. This blade is used solely for cutting all descriptions of circular work, and curves of every description. It may be useful to remark that this is the only shape of blade that will cut, with clearness and sharpness, curved lines through thick cardboard. The instrument next illustrated is called a knife compass, and is extremely valuable for cutting out circular architraves, &c., &c., doing its work in a way that the hand and knife could not equal, and with the least possible trouble. See illustration, page 36. They resemble, in some respects, an ordinary pair of compasses, but of a little stronger make than



the common. A is a moveable sweep of brass, to regulate the opening of the legs of the compasses, which, being opened to the requisite




THE KNIFE COMPASS.

width, are firmly held by tightening the thumb-screw, F. B, the moveable leg to which the

cutting-knife *c* is attached by means of a shoulder to the blade at *a*, and a socket at *h*, into which it fixes, and is secured by the screw at *d*. *e* and *i* are two screws working on the rod, *k*, on each side of the moveable bar, *b*.

By means of this contrivance the knife is always kept perfectly upright, and in consequence cuts perpendicularly through the cardboard. There may be several knives to fit in the socket for light and heavy work, but a blade of the same shape as that shown in the engraving, will be found sufficient for nearly every purpose. The instrument might perhaps be more useful if half as large again as represented. The dotted lines are given to show the instrument open wider, in order fully to illustrate the utility of the moveable leg at *b*. The method of using this instrument is this: Having a curve to cut, and having found the centre of the arc, place the point of the leg *l* within it, then adjusting the

moveable leg to the perpendicular by means of the screws *r* and *E*, stretch the legs to the requisite radius, and by gradually increasing the pressure on the blade, the curve may be cut with the most perfect ease and truth.



H L. Horizontal line.

## PART III.

### THE COMMENCEMENT AND FINISH OF A MODEL.

---

ASSUMING that the student has now procured the various instruments and materials for his work, and that he has also determined upon the design he intends in paper, the next thing necessary is to give him as far as it is possible by a book copiously illustrated, an exact description of the method of proceeding. We will therefore imagine a design which is to be modelled (see frontispiece), a Villa, in the domestic Italian style, for example; and taking it to pieces bit by bit, endeavour to raise it up again in renewed beauty and effect.

Having the four elevations, together with the

ground and roof plans, the latter being essential to show the position of the chimneys, skylights, &c., we take a common drawing-board, about the size of the intended model, and upon it strain as for a drawing that size, a piece of drawing cartridge, say an inch and a half wider all round than the intended model is to be. Upon this, when dry, draw an *outline plan* of the intended building, not putting in any internal walls, for these will not be required as this is only to form lines whereon to erect the intended building. To make it more readily to be understood we have given a sketch of the outline plan on page 45.

This being completed, we have now the edifice, as it were, set out. The next matter for consideration is the thickness of the walls; that is, the requisite thickness of paper we shall require. Suppose we take, as in the plan given, the outside reveal or recess back of the window frame,

**ELEVATIONS OF VILLA.**



**ELEVATION OF ENTRANCE.**




**SIDE ELEVATION.**



at four inches and a half; this would require four sheets of paper, but as it is always better to exaggerate slightly in modelling both projections and recesses, place six or even seven sheets together; paste them together in twos, putting them as pasted under the press, and afterwards, when nearly dry, paste them the full thickness required and subject them once more to the action of the press. The most convenient size of paper to work at for an ordinary-sized model will be made by doubling a sheet of the paper as first procured into four. On the paper becoming perfectly dry, the student must carefully draw each elevation of the building the full height from the ground line to the top of the blocking, being particular that every line both perpendicular and horizontal is perfectly true and square, and marking along faintly the lines for the cornice, strings, &c., &c., that may occur. This being done and the whole drawn in, of



course not drawing in the window frames but merely the outline of the square of the window, the side will present the appearance shown in the accompanying elevation, and which is merely sketched and not drawn to any scale.



A Lines for cornice.


C Ditto lower cornice.

B Lines of upper string.


D Ditto Plinth.

The four or more elevations having been drawn, proceed to cut out all windows, doors, and other openings cleanly and accurately. The windows and their frames must now be made and gummed at the back of the several openings; where panels occur paper of the same tint must be used, sometimes the pieces cut from the

# PLANS OF VILLA.



GROUND PLAN.



OUTLINE PLAN.

Scale 10 5 0 10 20 30 40 50 feet.

it the size of the window-opening, then lightly draw the frames in and cut them out, if the white paper of the under sheets should show where cut through sectionally, touch it along with a little burnt sienna or brown colour. You must now tint another sheet of the same description of paper blue or neutral, not in an even tint, but carelessly and artistically leaving bright lights; this when pasted as for the oak-paper two or three thicknesses, will form the backing to the frames. Then place the frames face down, on them gummed a sheet of mica; on that again the blue backing; the whole then to be put in the press, care being taken not exhibit too much pressure, otherwise you will have the backing bulge out. It may, perhaps, be thought that these thicknesses of paper for the frames and backing are unnecessary, and that one might serve as well; but from experience I can assert, that unless this method

**DETAILS No. 1.**



**ELEVATION OF ENTRANCE DOOR.**



**PLAN OF ENTRANCE DOOR.**



be adopted, that flatness the work should have, will not be obtained. It may also be as well here to caution the reader against pressing with too great a degree upon the cardboard when it is under the action of the press. If too great a pressure is given, the cardboard will become so hard as to resist all efforts of the knife to cut through it. The paper usually presses to a little less than an inch, to a scale of one-eighth of an inch to the foot; so that six thicknesses or sheets of paper will answer for four and a half of brickwork or stonework. The doors will be formed first from two thicknesses\* and backed with the same. This is for plainest description, but if mouldings are inserted in the panels, adopt the following :—

First draw the door with the extreme size of


\* One thickness, two thicknesses, three thicknesses, and so forth, will be used throughout, to express the number of sheets to be pasted together.

the opening of each panel, on a two-thickness sheet; on another two-thickness sheet, draw the same panels a size smaller; on a third two-thickness sheet, draw them a size smaller still; these being cut out and placed behind one another, and finally the backing; will admirably represent mouldings: by producing three separate lines round the inside of each panel. For work to  $\frac{1}{8}$  scale no further trouble will be necessary; but if larger, the mouldings must be formed before the door is gummed together, as hereafter described for the formation of mouldings in general. The doors, windows, and backs to all openings are now ready, but cannot be yet fixed till all the necessary mitreing is completed, which mitres will be wherever an outside angle occurs thus, fig. 1. (See page 53, figs. 1 and 2.)

In the inner angle (see fig. 2) no mitre is required; the end of one piece being cut square, they may be made to overlap one another. Lay


the piece, whatever it may be you wish to mitre, face down upon the cutting-board; and then at a distance (equal to the whole thickness of the

Fig. 1.



OUTSIDE ANGLE.

Fig. 2.



INSIDE ANGLE.


card-board) from the edge draw a line; and at a short distance back from this line sufficient to let the point of the knife touch it when held slanting to the required angle, fix the adjusting straight-edge previously described; screw firmly upon it, and cut through the paper at an angle of  $45^{\circ}$ , which will, of course, be by cutting from the line on the top side of the paper, A, to the extreme edge of the underside, B (see illustration page 55), which represents the side of a building, and the piece may be seen curling up as cut from the mitre. Great steadiness of hand, and



a few trials on waste cardboard are necessary before the operator will perform this skilfully. The straight-edge holding the paper firmly, it may be cut through at two or three strokes, observing to hold the knife always at the same angle. All mitreing work finished, affix the windows at the back, placing the whole under a slight pressure.\* Then the model must be blocked up. First cut a number of squares, all sizes, from waste or other cardboard; let them be perfectly square; cut these diagonally, and they will form the blocks to hold the work together at the angles. Now take any two sides that are to be joined at the mitred angle, and fix them accurately together with gum pretty thick, so that it may

\* As there are many little matters during the progress of a model requiring a slight pressure, a pressure sufficient to hold the pieces in their several places till dry, I have found weights answer very well. I have pieces of square lead from one pound upwards covered with paper; and by covering, the humble brick may be usefully pressed into this service.


dry while you hold each side in its place. When set, lay them down and work the others in a similar manner. Take now the outline plan, and having previously numbered the sides to correspond with the plan, fix them (by touching slightly their under edge with gum) to it, and



when all are in their places fix, at a distance apart of an inch and half or so, above one another the previously described blocking pieces with gum not so thick in consistency. To make our meaning perfectly plain, we annex an engraving of the appearance of an internal angle when at this stage of the proceedings. A piece of wood (deal) about  $\frac{1}{2}$  inch thick, should now be


attached to the model from one side to the other (see page 57). This is for the purpose of fastening the model, when completed, to its stand ; it may be blocked with waste pieces, such as the cuttings from doors, windows, &c., and gummed firmly.

SKETCH SHOWING THE WAY THE BLOCKING PIECES ARE  
INSERTED IN AN INTERNAL ANGLE.



Pieces or strips of cardboard should also be gummed along in the inside, at the level of the intended gutters of the house, to rest the roof upon. All portions of the work completed, we will now assume, are fitted together and in their places. The student will now be able to form some idea

# METHOD OF INSERTING THE WOOD STAY.



A A Cardboard angle stays. B B B B Wood stay by which the model is affixed to its stand by a screw passing through at C C. D E F G Sides of model.



of the general effect his work will have when finished; but there is yet more—much more—to be done, and work requiring a still further amount of skill, practice, and patience.

The two principal elevations are given to the same scale as the plan (page 41); but in order to insure our being understood, the principal portions of the details are given to a larger scale.

The cornice next demands our attention, a detail of which is given on page 61, fig. 1, and in order to model which we proceed thus, the numbers indicating the various pieces of which it is composed. No. 2 is a piece worked of the required thickness demanded by the depth of the cornice from A to B, and the necessary projection, in a sufficient series of lengths to go entirely round the building. Now, as this is to be cut through the several thicknesses of paper required, a method must be found out to hide the different layers that would consequently be exposed to


view; this is by cutting from one or two thicknesses a piece the whole length of the cornice, forming a fascia, 8, and coming slightly below the depth of the other under piece to 4; thus, while at the same time it hides the layers of paper, it forms the bed of the cornice.

The next members, Nos. 1, 3, 5, and 7, are formed, first by preparing the size and length on the square; secondly, by cutting off at any angle necessary to get as near to the mould as possible; and, lastly, forming the mould itself.

The manner of moulding being applicable to every description of either Italian or Gothic pattern, we proceed to describe it.

Procure from the comb-manufacturers some pieces of *ivory* of various sizes, and with different files, some round, some square, &c., file on one end of a square piece the *reverse* of the mould you require; smooth it well; and for greater power and convenience, fix it in a handle of wood.

# DETAILS No. 2.




- 1 Elevation and section of main cornice. 2 Elevation of window.  
 2a A detail of section through window. 3 Architrave mould.  
 5 Elevation of small window. 5a Section of small window.  
 6 Elevation of quoins. 7 Section and elevation of tower cornice.





Nos. 1, 2, 3, &c., &c., will be found generally available and useful in the formation of all kinds of mouldings, besides numbers of other shapes that will occur to the artist. The method of using the instrument is by indenting the pattern


## MOULDING TOOLS.



A, Handle with socket to secure the moulding tool (1).

B, Thumb-screw.

1, 2, 3, Moulding tools.



along the edge of the cardboard, guided by means of the straight-edge. The sharp arris left from the file upon the edge of the ivory mould, had better be slightly taken off, to prevent the paper being torn in its passage.


The circular pediment over windows (fig. 2, page 61) must be modelled on the flat, and the moulding returned at the ends. When each member is finished, they must be gummed up and bent to the required curve, over a circle of cardboard or a cylinder of wood, separately. The panels that occur form thus: Cut as before directed for doors, the extreme size of the opening, and at the back place the successive sizes and thicknesses to form the mouldings, indented into hollows or worked to rounds, &c., &c., by means of one or more of the moulding tools; to be backed last of all.

Commence the preparation of the quoins (fig. 6, p. 61) by cutting pieces the required thickness and width of both long and short quoins, and in long strips, with the *height* of each one marked up its length previously by the dividers.\* Cut first the

\* The small hair dividers, with the adjusting screw, will be found extremely useful in modelling work.

requisite splay at the edge of the quoin, along the whole length both sides. Cut where marked for height, and splay top and bottom. They are then finished, and may be at once fastened to the work.

The circular architraves must be formed by cutting, with the little instrument previously described as a knife-compass (page 36), circles of different diameters and thicknesses of paper suited to the mould to be represented; gum together while in the circle, as shown below, the



CIRCULAR ARCHITRAVES.

K Keystone. R Radius. H L Horizontal line.

horizontal divisional line being marked, and the radiating lines for the insertion of the keystones.

When dry cut off by the divisional line, and then the segments, by the lines at each side of the keystone. The key must be of paper sufficiently thick to allow of the highest mould of the architrave abutting against it, and either left plain, cut diamond-wise, or carved, or any other way the fancy may suggest or the design demand.

The cantalivers in tower (fig. 7, page 61) and main cornices (fig. 1, page 61) to be worked by preparing paper the required thickness; then procuring a piece of very thin copper or lead, mark on it with considerable accuracy the design of the cantaliver, and cut it out; you will thus have prepared a mould or templet, which you can place upon the cardboard, and by running a hard pencil round it, mark each one precisely the same in size.

Any portions of the dressings, &c., having curves in them, had better be cut with knife

No. 3\*; in fact, this is the only shape of blade which will leave the edge of a curved line after cutting, what is technically called "sweet."


The positions the cantalivers have to occupy along the cornice, must be checked along and regularly divided. Care must also be taken in gumming them in their places, as one out of place or leaning would immediately be detected by a correct eye, and mar completely the effect of the whole.

The architrave mould (fig. 3, page 61) next demands our attention. It will from our former description be readily understood that all mouldings are formed by representing in paper of various thicknesses their several component parts. Thus, in the mould last named, we have first the groundwork of or thickness from A to B; another thickness, forming the


\* In using this knife, care must be taken to hold it perfectly upright, nor lean it either to right or left.

sinking, from c to d; and finally, the mould, e to f. Square first, the required slant next cut from the edge, and lastly, the slant hollowed by means of one of the ivory moulding tools. The keystones and the blocks under the window sills are cut from paper the thickness required, then splayed down each way from the centre to the sides at *one* cut, and with a sharp knife. This operation must be performed with some dexterity, as it is important that the edges should be sharp and free from woolliness. This effect can only be obtained by giving one cut or slice in the direction required: for this purpose use knife No. 1, which will be found the best for this description of work. Some modellers use for this purpose a thin chisel with a keen edge; and of course all means in art are legitimate that produce the desired end; but we would recommend the use of the knife only, wherever possible, the modeller's object being to work with as few

**DETAILS OF WINDOWS. No. 3.**



**MORNING ROOM.**



**KITCHEN.**





tools as possible, and to trust much to his knife alone.


We have, in describing the method of working several important details connected with the building, and illustrated on page 61, been, we fear, somewhat premature, and have not sufficiently urged upon the student the necessity of preparing his groundwork for these details in a perfectly accurate manner. For, as it is well known, no colouring, however fine, will in a picture make up for bad and incorrect drawing, so in a model, walls out of square or windows and other apertures ill-cut will not present the wished-for appearance, though all the details be most skilfully and beautifully modelled. Draw in all doors, windows, &c., &c., with a very hard pencil, in order that the lines may be as fine as possible, and cut them out with knife No. 1, or No. 2, whichever may be considered most suitable to the size of opening it is required to

cut ; the knife No. 3, as before observed, being used exclusively for curved and circular work. In cutting out the windows, hold your knife perfectly upright ; and, as you arrive at the end of the cut, let the *edge* of the blade be perpendicular, thus avoiding cutting past the line. In cutting through thick, or indeed even through one thickness of paper, do not be too anxious to sever the piece with one cut, as this way of proceeding is almost sure to cause unevenness of line. But commence by *drawing* a line, as it were, in the required direction ; that the rule may guide it accurately, press but slightly at first ; and as the track of the knife gets deeper, exert more pressure. Simple as this direction may appear, it is nevertheless of the utmost practical utility, as will readily be found upon trial, as it is only by these means that the paper will be left at the edge clean, sharp, and even.


The next object we would call attention to is



**ELEVATION.**



**PLAN.**




**DETAILS OF GREENHOUSE. No. 1.**



the Greenhouse, page 73, and state that there are two ways of modelling this very general appendage to a modern mansion. The first and the simplest method is to form the backing of blue paper behind the mica. The other, by doing away with the blue backing, and allowing the mica to remain transparent. The former method saves some amount of labour; but the latter being in our opinion the best and most artistic method, we shall proceed to describe it: First form the pilasters (you will require double the number than for the opaque backing), and cut them in their length from A to B (see elevation, page 73), from the commencement of the base mouldings to the underside of those of the cap. The way of proceeding in modelling cap and base will be readily understood from the accompanying sketch, where it will at once be seen better than we can describe. The best way to cut them is as if they were a window or opening, cutting the piece out of the centre at A, after having moulded

the edge all round. Then dividing them into two along the line D L as below, fix them in their respective places. The angle ones must be double,




D L Divisional line.

to avoid having to mitre them. A piece of mica or thin glass cut to the size of the one side is now taken, and the pilasters and other portions, divisional bars, &c., are gummed to it, on both sides; and when with the end it is finished, let it occupy its intended position on the outline plan.

Now proceed to the roof, to be constructed really of iron and glass, to be modelled of paper and mica: First, bend round a paper or other cylinder the piece of mica for the roof, and proceed to cut a number of strips of cardboard for the ribs, which may be coloured any suitable tint.

**DETAILS OF GREENHOUSE. No. 2.**



**PART ELEVATION.**

**Scale . . . .  $\frac{1}{4}$  inch one foot.**







These are then to be affixed in their places, as shown upon the drawing, some in thicker, others in thinner paper. A ledge of cardboard must be left at the back of the blocking, and also on the same level against the side of the house; this will be for the purpose of resting the roof upon.\* The cornice will be constructed in the manner described for the others; the pieces on the frieze c, c, c (page 78) will be placed on the required thickness for the return, but the return of the cornice must be cut in it. The plinth must now be moulded, cut, and fixed; and the whole is complete.

Chimneys, those great ornaments to a house, at least they should be rendered so, but, alas! for the taste of some of our modern architects, are far more frequently the reverse, and what in able hands and with judicious treatment would prove a crowning feature and a material

\* This description is for a circular roof; that, however, in the engraving represents a flat hipped roof. The method of proceeding is the same, except that for the latter no cylinder is required.

assistance to the design, becomes a glaring error and ruins the whole. So much for the architect : but should he fortunately possess the ability and taste to produce those necessities to our comfort, with equal credit to himself and benefit to the design, how often do we see his work marred by the introduction of Messrs. Somebody's patent never-failing revolving smoke preventer ; a hideous monster of some seven feet high, whirling and screeching upon the slightest appearance of wind. As our little Handbook has its mission to instruct in the Art of Modelling an architect's production, and as smoke-jacks are but little indebted to him for their uneasy existence, we beg to apologise for this digression, and resume our original topic. Details of the chimneys will be found upon page 81 and 83 ; for the body of the chimney use two thicknesses, and it will not be found necessary to mitre the join ; for, if even ordinary care be taken, the union will be scarcely perceptible, while the

labour will be considerably diminished. Form any strings, cornices, &c., &c., that occur, by cutting the piece flat, and then cutting the square out of the middle to admit of the shaft, slip it over the shaft or body of the chimney, till it arrives at the position required by the design, where it is at once to be secured in its place.



DETAILS OF CHIMNEYS.


Perhaps our meaning may be rendered clearer by

the accompanying illustration. A represents the cornice prepared in the manner described, and only requiring to be fixed in its place. B, the shaft or body of the chimney over which the cornice is to be slipped till it arrives at the dotted lines; the chimneys may be fixed to the roof (shortly to be described) in the following manner: Should the chimney come on the roof lower down than the ridge, the bottom of the shaft will have to be cut to the angle required by the rake of the roof only; but should the chimney be cut into by the ridge, then the angle will follow that of the roof on both sides, diverging from the apex. For illustration of this we give the annexed sketches, page 83.

A represents a chimney, the base of which is cut simply *one way*, to suit the slope of the roof. B, a chimney into which the ridge cuts, and the angle cut both ways from the apex. It will, as a general rule, be found better to put chimneys

together with thin paper, even in the smallest models, a squareness being thus produced not to be obtained otherwise. The base to be formed out of thickness equal to the projection, and treated in (as regards fitting it to the roof) a similar manner to the shaft, so that if the rake of shaft

## DETAILS OF CHIMNEYS.



had chanced not to have been truly cut, there is no need to throw it away, as it could easily be blocked under with small pieces till straight, the base hiding all defects underneath. The method of working the strings, cornices, &c., has already

been fully described in those for the tower and main building. Figs. 1 and 7, page 61.

Our model now draws near to its completion. We had arrived at a stage ready for the roof, but stopped for the preparation of the chimneys, in order that when the roof was completed, they might be at once fixed in their respective places. The roof may be either scored, or gauged with paper strips overlapped. The groundwork for either method will be prepared in the same manner. First cut, as if for a lid or top to fit the inside of the model, a strong piece of cardboard; let it be just so that it will slip into its place between the walls, but be prevented slipping down by the strips or ledge on the level of the gutter, as described for Greenhouse, page 73.

Sections must now be taken in various parts, through the roof, to ascertain the length of the respective sides. Thus if the angle  $A B C$  (see fig. 1, page 85) represents the rake of the roof, the length

# DETAILS No. 4.




Fig. 1.

D D BOTTOM PIECE.




Fig. 2.

B Bottom piece. C Cornice. L Ledge. s s s Slates. T Top piece. w Wall.  
The cross hatching shows the number of separate pieces the cornice is composed of.




Fig. 3.

ROOF PLAN.





of the side will be found from A to B and B to C. The sides thus formed must be splayed to fit at the valleys, apex, &c., and at the base splayed and fixed to the top piece on which the roof plan has been drawn, observing to leave space enough all round for the gutter. If the pieces on which the sections have been drawn are cut out, they will answer for internal stays to the roof.

The roof plan is given upon page 85, fig. 3, as also an outline section for the finishing of the roof, fig. 2, page 85 ; it will explain itself. The lead flat will be formed by the bottom piece, but it must be covered by a paper resembling in tint that of the lead itself. When the groundwork of the roof is completed, it must be covered in imitation of slates by one or other of the previously-mentioned methods. We will, however, describe both, leaving the reader to use his own judgment as to which he may adopt, our preference being for the strips of overlapping

paper. In the simple scoring, proceed to cut out of the slate tinted paper pieces accurately fitting to the groundwork of the roof, then with the knife handle score these sides along, as you would ink in the roof lines in a drawing, closer at the ridge, becoming wider at the base, and parallel to each other. The latter by cutting layers of paper, gauged decreasing in size as before directed, fixing them to the ground-work of the roof beginning at the base, and overlapping them about  $\frac{1}{16}$ th of an inch; after all, submitting to the press. The roof assumed to be finished, affix the chimneys, generally make good all imperfections, &c., and the model is ready for removal to its final destination; cut therefore the paper it was built upon from the board, and also tear from the bottom edges the paper that may have adhered to it, holding it by the wood stay.

Prepare a piece of dry wood about two or

three inches wider all round than the building itself, cover it with cloth or velvet, the latter preferable, the best colour green, and cut a small groove out of the upper edge; this is to receive the glass shade, which construct thus: procure five pieces of glass, the sizes rendered necessary by your stand to form a square or oblong shade, and fasten all together by means of strips of thin paper and gum (the dull gold paper to be procured in sheets at any of the artists' repositories will look best) at their edges. The model must now be secured to the stand, for which purpose the piece of wood mentioned at page 56 was inserted, a hole is drilled through the bottom of the stand, and a screw passed through it into the wood stay. Do not screw the model down too tightly upon the stand, or you may force away the stay from its fastenings and destroy your work.

We have now described all the necessary materials and manipulations to complete in every respect a model similar to the mansion given in

the illustrations, and which, though containing the general detail of a building of that description, was wanting in numerous varieties of detail that will occur in many other buildings of the same class more ornate and considerably more elaborate in design than our example.

While all our attention is being turned towards Italian architecture, Gothic must not be forgotten, and though the general method of procedure is the same for both, yet there are numerous things which exist only in the latter style, and in consequence demand separate instructions. In order, therefore, that nothing shall escape being described in the various styles, that the student may have nothing to retard his operations, we append the methods of working the various details in the form of an illustrated glossary, the alphabetical arrangement of which will, we think, enable the student more readily and quickly to find the particular information he may require.

## PART IV.

### HINTS ON LANDSCAPE GARDENING ; LAYING OUT GROUNDS, &c.

---

WE have, as yet, proposed to finish the model in the plainest and most simple way, completely unaided and unadorned by the adjuncts of gardens or trees. And yet, that models are frequently considerably improved in appearance by these imitations of natural objects, when taste and skill go hand in hand, will be admitted by all, but we often see them completely spoiled by such additions. It is indeed somewhat difficult to say how far we may venture with propriety upon this path, and where to draw the line requires some tact ; we will not, therefore, lay down any rule absolutely as

to how far the laying out of grounds and the modelling of the trees, &c., may be admissible, only giving some instructions for modelling the objects themselves. And though the grounds are laid out, the picturesque undulations of the surface, the ponds, flower-beds, arcades, terraces, lawns, shrubs, and trees, faithfully represented, let it not for one moment be supposed that by so doing we render what was before a work of art, a mere toy. Far from it. We do not wish the reader, when he thinks of a model, to remember those of York Minster, or Strasbourg Cathedral, and which, borne aloft upon the shoulders of some wandering Italian, tempt the vulgar by the rich colours of the stained glass inserted in their chalk sides, and brilliantly illuminated by the light of a farthing candle placed within; or of the grounds, as bearing any resemblance to those interesting toys representing a "*castle in cork*," about an inch high,

whose clinging ivy is represented by one of the largest species of moss, and in whose luxurious gardens bloom roses two inches in diameter, roses which should have decked some matron's cap, but which for the nonce were pressed into this more noble service. But, to proceed. Balusters of grotesque, Elizabethan, or other patterns, when cut out of the solid stone, must be made by gumming the paper in different thicknesses, till that required is obtained, carefully drawing the pattern, and then cutting out with knife No. 3. Turned work, as circular pedestals for statues, sundials, gate-piers, balusters, &c., cannot be successfully imitated in paper, but are better turned in wood of some light colour, and then tinted with body colour to the required shade; all work of the same description that is *square* may be constructed in exactly the same manner as before described for chimney-stacks. For a representation of lawns and grassy slopes, meadow, &c., we may take



white velvet, and tint it to any required shade, or use cloth which can be obtained any shade of green, or even flock paper may be procured, which, when cleverly laid on the work, gives an excellent imitation of grass; but of all these methods, velvet tinted will be found the most effective and best. Water, represent with looking-glass, or with mica, to the back of which is gummed paper of suitable tint for the situation of the water. For rocks, grottoes, &c., take stout white paper, and thoroughly soak it in water until it is rendered quite pliable, and then with the fingers, pieces of wood, or any thing that may suggest itself as being useful, mould or model it to the required shapes fancy or skill may suggest, and afterwards tint it to resemble nature. An effect better still may be obtained by gumming it, when perfectly dry, with thick gum, and then dusting or sprinkling it with fine sand, which may be procured of various shades.

This method adopt also for walks, carriage-drives, or any place where a representation of road, or gravel, may be required. Cut out your flower-beds in thin cork, and then burn the upper surface; this will give the appearance of rich mould, or earth, and also serve as a good groundwork to stick the shrubs and flowers into. In your trees, rather aim at a general or suggestive effect, than at much minutiae of detail; procure pieces of twigs, and shape them for the trunks and branches, and then gum on them the smallest-leaved moss, in good outline to represent nature; this moss will, when perfectly dried, bear tinting well. Flower-patches, the same moss with a bit of bright scarlet, or other paper, here and there gummed among it.

We have now given sufficient general instructions to enable the student to proceed with this branch, should his fancy lead him; and with these suggestions, and his own practice, he may

in a short time be enabled to imitate successfully the quaint gardens of the Elizabethan period, or the more natural taste evinced in the landscape gardening of our own times.

. . . . . "Does airy fancy cheat  
My mind well pleased with the deceit?  
I seem to hear, I seem to move,  
And wander through the happy grove,  
Where smooth springs flow, and murmuring breeze  
Wantons through the waving trees."

CREECH.

## PART V.



### A GLOSSARY

CONTAINING THE METHODS OF WORKING VARIOUS  
DETAIL, &c., NOT HITHERTO DESCRIBED.


---

#### A.

ARCH.—As a general rule, every description of arch may be successfully modelled by means of the knife-compass; each separate moulding that occurs must consist of separate pieces of paper, the edge of which has been moulded by one or other of the means described, and these layers gummed over one another when finished. To make our meaning clearer, in fig. 1 next page, a section of a cornice is given, as illustrating the method to be adopted for arches. It will here be seen that it is composed of six separate pieces, or, more properly speaking, thicknesses, for each portion will be made of the number of thicknesses required by its

depth ; No. 1, the fillet, square, No. 2, the cyma recta, first splay, as shown by the dotted line ; and then press with the moulding tool to the required shape, and thus proceed with all the other members.

This cornice is not drawn to any scale.



No. 1 Fillet.	No. 2 Cyma recta.	No. 3 Fillet.
No. 4 Cassetto.	No. 5 Fascia.	
No. 6 Continuation of fascia.	No. 7 Bed mould.	

Where deep hollows occur, as in Gothic mouldings, a different method must be adopted, see fig. 2, the moulding for a Gothic window jamb ; here the deep hollows are constructed by bending thin paper to the required curve, and gumming it in the right angles, or other angles required. A and B represent the outside walls of the work, and c c c c the various angles required by the mouldings. As will be seen, the other mouldings

are formed on the ends of angle-pieces, in the same manner as adopted for the cornice.





Fig. 2.



**ARCHITRAVE.**—In forming these, the same method may be adopted as for cornices, cutting the mouldings separately, and laying them one over the other in the order in which they come. Circular architraves are easily and beautifully cut with the knife-compass.

**ACANTHUS.**—The method of modelling the leaves of this plant, so much used in ornamentation, will be afterwards described under the general head of ornaments.

**ASHLAR.** — In representing work of two kinds, namely, quoins of dressed work, and filling in of random tooled ashlar:—Draw the quoins in with a H H H pencil, score in the ashlar, and tint as may be desired.



RANDOM ASHLAR.

**ASTRAGAL.**—First cut your paper square, thus—; next bevel the edge thus , and then, with one of the hollow ivory moulding tools run along the edge by pressure, give the intended round.


**ACROTHERIA**—May be modelled in exactly the same manner as previously described for chimney shafts (see page 80, *ante*).

## B.

**BARGE BOARD.**—First determine on the thickness your board is to be, and then let the paper for it be pressed closer together than that used for ordinary work; carefully draw the pattern, and cut out with knife No. 3, splaying the tracery with knives Nos. 1 and 2, and smoothing with an ivory or agate burnisher.

**BARGE BOARD.**

**BUTTRESS.**—If they are to a large scale, say quarter-inch, one foot, they are best boxed out; the angles carefully and accurately mitred. Less scale, they may be boxed out of double thickness, as described for chimney shafts; or, if very small size, they may be cut from the solid.

**SIDE VIEW.****FRONT VIEW.**

**BALUSTRADE.**—Model the capping as described for



cornices, with the exception, this will be worked upon both faces.

**BLOCKING.**—To a cornice. This, if large, is best constructed by being boxed out. If small in size, cut them out of the solid.

**BRACKET.**—Brackets in Gothic work are to be constructed in layers, in a similar manner as described for cornices ; other brackets may be cut from the solid paper, first by making a pattern, or template, in thin tea lead, or sheet copper, and marking round the edge upon the paper, uniformity of size being thus ensured.

### C.

**CORNICES.**—The construction of cornices is fully described in that of the House, illustrated, and also under the head of Arch, where a cornice is described as illustrating the formation of moulded arches.

**COINS, or Quoins ;** see those described for House, page 64, *ante* ; also Ashlar-work.

**COPING.**—If the coping be small scale, cut from the solid by the adjusting straight-edge ; otherwise they are better boxed out.


**CRESTING.**—Proceed in much the same manner as

described for barge-boards ; use a template to save trouble in pencilling out, and cut with knife No. 3 ; three thicknesses are ample for eighth scale work.

CUSPS.—See description of Tracery ; window-cusps being circular work, No. 3 knife must be used.

CORBEL.—Refer to Cantilevers in House Tower Cornice, the method of modelling being the same, except such as are composed of a series of horizontal mouldings, in which case proceed as for cornices.

CONSOLE.—The console given for example is composed vertically of five separate pieces ; horizontally of



two, each separate part receiving its proper form, and when completed, gummed together.

CAPITAL, CORINTHIAN.—We choose for illustrating the method adopted for modelling capitals, a Corinthian one, as most useful for our purpose. The example given is from the Temple of Vesta, at Tivoli, a beautiful

and peculiar example, to model which proceed thus :



A A A Flowers in the abacus.    1 2 3 Abacus.    B B Volutes.  
 C C Caulicoles.    C\* Bell.    1 2 3 Astragal.    D D D Flutes.

Compose the abacus of three layers, 1, ovolo, 2, fillet, 3, cyma ; then the bell of the capital must be turned out of some close-grained wood, and attached to the astragal, composed of three pieces, 1, fillet, 2, astragal, 3, fillet. The leaves are then to be modelled, as described under the head of ornaments, also the flower in the abacus ; the volutes and caulicoles in a similar manner to that described for consoles. When all are prepared, they must be fixed most accurately in their places. The bell of the capital must be tinted previously, to resemble in colour the rest of the work.

**COLUMN, CIRCULAR.**—This description of columns must be formed out of very thin paper, rolled as close as possible to the required lengths and diameters, thinning the paper at the extreme edge with a very sharp knife to conceal the join. If the columns are too small to be cleverly rolled, they may be turned as described for balusters; should the columns (as in classic work,) diminish, then procure a wood core to roll the paper round, and when the paper is gummed and dry, withdraw the core. It will now be obvious that combinations of various descriptions occurring so frequently in Gothic work, may easily be represented as this column in plan, being nothing more than four rolls joined together.



If the columns are too small for paper, turn shafts, bases, and caps at once; by this means much unnecessary trouble will be saved, and a superior effect produced.

#### D.

**DENTILS.**—Model dentils in the same manner as previously described for brackets, cantilevers, &c.

**DOME.**—Whatever the shape of the dome you wish to model may be, a pattern on which to form it had

best be turned in wood ; this forms a basis upon which the paper casing may remain until dry, and then the mould may be removed. It has not been thought necessary within the limits of this work to include the development of the various shapes of domes and cupolas, the student being deemed master of this branch of science. If, however, he should not be, any work on practical geometry will supply his wants.

DOORS.—A copious description of the manner of modelling doors is given in those described for the House, page 51, *ante*.

#### F.

FLUTES.—In order to flute a column, we proceed thus : first roll the column up as before described, taking care to have it smaller than if plain, to allow the fluted piece to make up the required diameter ; then prepare a piece of paper (one thickness will do), cut it of sufficient size to go once round the column, and join exactly ; upon this piece carefully space or mark out the divisions of the flutings. Now procure a piece of soft straight-grained *deal*, perfectly free from knots, and with some blunt, round-headed instrument (one of the modelling tools, or a piece of ivory filed smooth,)

indent the wood with a groove the exact length of the required flute, upon which (the paper having been previously *damped* only), press it into the wood groove all along the flute with the same tool the groove was made with, and so proceed with each in succession, gumming them to the column when dry.

## H.

HOLLOWS.—In forming hollows in mouldings, &c., if large, proceed as described under the head of Arch; if small, first cut by means of the “adjusting straight-edge,” an angle, thus, **V**; and then with a curved ivory tool give it the required concavity by pressure along the whole length of the previously cut angle.

HOOD MOULD. — These may be cut with the “knife-compass,” and the mouldings worked by fitting a piece of ivory filed to the required form in lieu of the knife; they must be slightly gummed upon the under-side to the cutting-board, to keep them steady while being worked.

## I.

IRONWORK.—May be represented in either paper, tea-lead, thin sheet copper, or wire, depending on size

and form ; perhaps the easiest and best material for general purposes is tea-lead, *i. e.*, the lead with which the tea chests are lined.

### O.

ORNAMENTS.—Under this head is included every description of foliage, leaves, &c. All the leaves, &c., must be carefully drawn and cut out, and then indented on either side, as concavity or convexity is desired, in a similar manner to the operation of fluting a column, with the different *ivory* modelling tools on a piece of soft yielding deal. Bosses, crocketts, finials, festoons, wreaths, in short every description of foliage, and even sculpture in bas-relief, may be beautifully modelled by these simple means.

### T.

TRACERY WINDOW.—The general method of modelling windows of this description is very simple, but the practice difficult. First, paper upon which you intend to cut out any tracery, must be *pressed* closer together than that used for ordinary work, so as to afford more assistance to the knife when cutting on

the splay. Having drawn the design of your window, proceed to cut out all the interstices with knife No. 3; then splay down from the nosing with knives Nos. 1 and 2, as each may be found useful, cutting through with one stroke, or rather with a succession of short strokes right through on the slant, boldly and without leaving a jagged edge; afterwards smooth your work with ivory or agate. You had better place the pieces that came from between the mullions while cutting the splay, in their places again between the mullions, to offer resistance to the knife and prevent them bending. The eyes may be successfully formed by packing-needles of diamond shape, fixed in a handle.

END OF THE GLOSSARY.





## TO THE READER.

---

It will have afforded the Author sincere gratification if the contents of this little work have found favour in the eyes of the Reader, and have been a ready help to him in his efforts in Architectural Modelling. Next to the pleasure of learning, is that of imparting knowledge. The Author has endeavoured, to the best of his ability, to render all his instructions clear and practical, at the same time divesting them of all unnecessary technicalities, and rendering them as terse as possible.

FINIS.

**LONDON :**  
**BRADBURY AND EVANS, PRINTERS, WHITEFRIARS.**

# CATALOGUE

OF

## RUDIMENTARY, SCIENTIFIC, EDUCATIONAL, AND CLASSICAL WORKS

FOR COLLEGES, HIGH AND ORDINARY SCHOOLS,  
AND SELF-INSTRUCTION;

ALSO FOR

MECHANICS' INSTITUTIONS, FREE LIBRARIES, &c., &c.,

PUBLISHED BY

**JAMES S. VIRTUE, CITY ROAD & IVY LANE.**

---

\*.\* THE ENTIRE SERIES IS FREELY ILLUSTRATED ON WOOD  
AND STONE WHERE REQUISITE.

---

*The Public are respectfully informed that the whole of  
MR. WEALE'S Publications, contained in the present Catalogue,  
have been Purchased by JAMES S. VIRTUE, and that all future  
Orders will be supplied by him at the above addresses.*

---

*\*.\* Several additional Volumes, by Popular Authors, are in  
preparation, and will shortly be ready for delivery.*

---

### RUDIMENTARY SERIES.

- |   |         |
|---|---------|
| 2. NATURAL PHILOSOPHY, by Charles Tomlinson . . .   | 1s.     |
| 3. GEOLOGY, by Major-Gen. Portlock, F.R.S., &c. . .   | 1s. 6d. |
| 6. MECHANICS, by Charles Tomlinson . . .  | 1s.     |
| 12. PNEUMATICS, by Charles Tomlinson . . .  | 1s.     |
| 20, 21. PERSPECTIVE, by George Pyne, 2 vols. in 1 . . .   | 2s      |
| 27, 28. PAINTING, The Art of; or, A GRAMMAR OF<br>COLOURING, by George Field, 2 vols. in 1 . . .                                    | 2s      |
| 36, 37, 38, 39. DICTIONARY of the TECHNICAL TERMS<br>used by Architects, Builders, Engineers, Surveyors, &c.,<br>4 vols. in 1 . . . | 4s      |
| In cloth boards, 5s.; half morocco, 6s.   |         |
| 40. GLASS STAINING, by Dr. M. A. Gessert, With an<br>Appendix on the Art of Enamelling . . .  | 1s      |

- 
41. **PAINTING ON GLASS**, from the German of Emanuel O. Fromberg . . . . . 1s.
- 69, 70. **MUSIC, a Practical Treatise**, by C. C. Spencer, Doctor of Music, 2 vols. in 1 . . . . . 2s.
71. **THE PIANOFORTE**, Instructions for Playing, by C. C. Spencer, Doctor of Music . . . . . 1s.
- 72 to 75\*. **RECENT FOSSIL SHELLS** (A Manual of the Mollusca), by Samuel P. Woodward, 4 vols. in 1, and Supplement . . . . . 5s. 6d.
- In cloth boards, 6s. 6d.; half morocco, 7s. 6d.
83. **BOOK-KEEPING**, by James Haddon, M.A. . . . . 1s.
84. **ARITHMETIC**, with numerous Examples, by Professor J. R. Young . . . . . 1s. 6d.
- 84\*. **KEY TO THE PRECEDING VOLUME**, by Professor J. R. Young . . . . . 1s. 6d.
96. **ASTRONOMY, POPULAR**, by the Rev. Robert Main, M.R.A.S. . . . . 1s.
- 101\*. **WEIGHTS AND MEASURES OF ALL NATIONS**; Weights of Coins, and Divisions of Time; with the Principles which determine the Rate of Exchange, by Mr. Woodhouse, F.R.A.S. . . . . 1s. 6d.
103. **INTEGRAL CALCULUS**, Examples of, by Prof. J. Hann . 1s.
112. **DOMESTIC MEDICINE**, for the Preservation of Health, by M. Raspail . . . . . 1s. 6d.
131. **MILLER'S, FARMER'S, AND MERCHANT'S READY-RECKONER**, showing the Value of any Quantity of Corn, with the Approximate Value of Mill-stones and Mill Work . . . . . 1s.

(*In Preparation.*)

**PHOTOGRAPHY. A New Manual.**

---

## PHYSICAL SCIENCE.

1. **CHEMISTRY**, by Professor Fownes, F.R.S., including Agricultural Chemistry, for the use of Farmers . . . 1s.
- 4, 5. **MINERALOGY**, with a Treatise on Mineral Rocks or Aggregates, by James Dana, A.M., 2 vols. in 1 . . . 2s.
7. **ELECTRICITY**, an Exposition of the General Principles of the Science, by Sir William Snow Harris, F.R.S. . 1s. 6d.
- 7\*. **GALVANISM, ANIMAL AND VOLTAIC ELECTRICITY**; A Treatise on the General Principles of Galvanic Science, by Sir William Snow Harris, F.R.S. . 1s. 6d.
- 8, 9, 10. **MAGNETISM**, Concise Exposition of the General Principles of Magnetical Science and the Purposes to which it has been Applied, by the same, 3 vols. in 1 . 3s. 6d.
- 

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

- 11, 11\*. **ELECTRIC TELEGRAPH, History of**, by E. High-  
ton, C.E. . . . . 2s.
133. **METALLURGY OF COPPER**, by R. H. Lamborn . . . 2s.
134. **METALLURGY OF SILVER AND LEAD**, by Dr.  
R. H. Lamborn . . . . . 2s.
135. **ELECTRO-METALLURGY**, by Alex. Watt, F.R.S.S.A. 1s. 6d.

## BUILDING AND ARCHITECTURE.

16. **ORDERS OF ARCHITECTURE**, and their *Æsthetic*  
Principles, by W. H. Leeds . . . . . 1s.
17. **STYLES OF ARCHITECTURE**, by T. Bury . . . 1s. 6d.
- 18, 19. **ARCHITECTURE, Principles of Design in**, by E. L.  
Garbett, 2 vols. in 1 . . . . . 2s.
22. **BUILDING, the Art of, in Five Sections**, by Edward  
Dobson, C.E. . . . . 1s.
- 23, 24. **BRICK AND TILE MAKING**, by E. Dobson, C.E.,  
2 vols. in 1 . . . . . 2s.
- 25, 26. **MASONRY AND STONE-CUTTING**, with the Prin-  
ciples of Masonic Projection Concisely Explained, by H.  
Dobson, C.E., 2 vols. in 1 . . . . . 2s.
30. **DRAINING and SEWAGE OF TOWNS and BUILD-  
INGS**, Suggestive of Sanatory Regulations, by G. D.  
Dempsey, C.E. . . . . 1s. 6d.  
(With No. 29, **DRAINAGE OF LAND**, 2 vols. in 1, 2s. 6d.)
35. **BLASTING ROCKS, QUARRYING, AND THE QUAL-  
ITIES OF STONE**, by Lieut.-Gen. Sir J. Burgoyne,  
Bart., G.C.B., R.E. . . . . 1s. 6d.
42. **COTTAGE BUILDING, or Hints for Improving the**  
Dwellings of the Labouring Classes . . . . . 1s.
44. **FOUNDATIONS AND CONCRETE WORKS, A Treatise**  
on, by E. Dobson, C.E. . . . . 1s.
45. **LIMES, CEMENTS, MORTARS, CONCRETE, MAS-  
TICS, &c.**, by G. R. Burnell, C.E. . . . . 1s.
- 57, 58. **WARMING AND VENTILATION**, by Charles Tom-  
linson, 2 vols. in 1 . . . . . 2s.
- 111\*. **ARCHES, PIERS, AND BUTTRESSES**, the Principles  
of their Construction, by William Bland . . . 1s. 6d.
116. **ACOUSTICS; the Distribution of Sound**, by T. Roger  
Smith, Architect . . . . . 1s. 6d.
123. **CARPENTRY AND JOINERY, a Treatise founded on**  
Dr. Robison's Work . . . . . 1s. 6d.
- 123\*. **ILLUSTRATIVE PLATES to the preceding** . . . 4s. 6d.

124. ROOFS FOR PUBLIC AND PRIVATE BUILDINGS, founded on Dr. Robison's Work . . . . 1s. 6d.  
 124\*. IRON ROOFS of Recent Construction — a Series of Descriptive Plates . . . . 4s. 6d.  
 127. ARCHITECTURAL MODELLING, Practical Instructions in the Art . . . . 1s. 6d.  
 128, 129. VITRUVIUS ON CIVIL, MILITARY, AND NAVAL ARCHITECTURE, translated by Joseph Gwilt, Architect, with Illustrative Plates, by the Author and Joseph Gandy, 2 vols. in 1 . . . . 5s.  
 130. GRECIAN ARCHITECTURE, Principles of Beauty in, by the Earl of Aberdeen . . . . 1s.  
 132. ERECTION OF DWELLING-HOUSES, with Specifications, Quantities of Materials, &c., by S. H. Brooks, 27 Plates . . . . 2s. 6d.
- 

## MACHINERY AND ENGINEERING.

33. CRANES AND MACHINERY FOR LIFTING HEAVY WEIGHTS, the Art of Constructing, by Joseph Glynn, C.E. . . . . 1s.  
 34. STEAM ENGINE, by Dr. Lardner . . . . 1s.  
 43. TUBULAR AND OTHER IRON GIRDER BRIDGES, including the Britannia and Conway Bridges, by G. D. Dempsey . . . . 1s.  
 47, 48, 49. LIGHTHOUSES, their Construction and Illumination, by Allan Stevenson, C.E., 3 vols. in 1 . . . . 3s.  
 59. STEAM BOILERS, their Construction and Management, by R. Armstrong, C.E. . . . . 1s.  
 62. RAILWAYS, Principles of Construction, by Sir E. Stephenson . . . . 1s. 6d.  
 62\*. RAILWAY WORKING IN GREAT BRITAIN AND IRELAND, Statistics, Revenue, Accounts, &c., by E. D. Chattaway . . . . 1s.  
 (Vols. 62 and 62\* bound in 1, 2s. 6d.)  
 67, 68. CLOCK AND WATCH MAKING, including Church Clocks and Bells, by Edmund Beckett Denison, M.A., with an Appendix, 2 vols. in 1 . . . . 3s. 6d.  
 78, 79. STEAM AND LOCOMOTION, on the Principle of connecting Science with Practice, by John Sewell, L.E. 2 vols. in 1 . . . . 2s.  
 78\*. LOCOMOTIVE ENGINES, a Treatise on, by G. Drysdale Dempsey, C.E. . . . . 1s. 6d.  
 79\*. ILLUSTRATIONS TO THE ABOVE . . . . 4s. 6d.
- 

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

- 98, 98\*. **MECHANISM AND THE CONSTRUCTION OF MACHINES**, by Thomas Baker, C.E.; and **TOOLS AND MACHINES**, by James Nasmyth, C.E., with 220 Woodcuts . . . . . 2s. 6d.
114. **MACHINERY**, its Construction and Working, by C. D. Abel, C.E. . . . . 1s. 6d.
115. **ILLUSTRATIVE PLATES TO THE ABOVE**, 4to. 7s. 6d.

## CIVIL ENGINEERING.

- 13, 14, 15, 15\*. **CIVIL ENGINEERING**, by Henry Law, C.E., 3 vols.; with a Supplement by G. R. Burnell, C.E.; 4 vols. in 1 . . . . . 4s. 6d.
29. **DRAINING DISTRICTS AND LANDS**, the Art of, by G. D. Dempsey, C.E. . . . . 1s.  
(With No. 30, **DRAINAGE AND SEWAGE OF TOWNS**, 2 vols. in 1, 2s. 6d.)
31. **WELL-SINKING AND BORING**, by John G. Swindell, revised by G. R. Burnell, C.E. . . . . 1s.
46. **ROAD-MAKING**, the Construction and Repair, by S. C. Hughes and H. Law, C.E., and Gen. Sir J. Burgoyne, Bart., G.C.B., R.E. . . . . 1s. 6d.
- 60, 61. **LAND AND ENGINEERING SURVEYING**, by T. Baker, C.E., 2 vols. in 1 . . . . . 2s.
- 63, 64, 65. **AGRICULTURAL BUILDINGS, FIELD ENGINES, MACHINERY, AND IMPLEMENTS**, by G. H. Andrews, 3 vols. in 1 . . . . . 3s.
66. **CLAY LANDS AND LOAMY SOILS**, by Professor Donaldson, A.E. . . . . 1s.
- 77\*. **ECONOMY OF FUEL**, by T. S. Prideaux . . . . . 1s.
- 80\*, 81\*. **EMBANKING LANDS FROM THE SEA**, with Examples of actual Embankments and Sea Walls, by John Wiggins, F.G.S., 2 vols. in 1 . . . . . 2s.
- 82, 82\*. **POWER OF WATER**, as applied to the Driving of Mills, and Giving Motion to Turbines, and other Hydrostatic Machines, by Joseph Glynn, F.R.S., C.E. . . . . 2s.
- 82\*\*, 83\*, 83 bis. **COAL GAS**, its Manufacture and Distribution, by Samuel Hughes, C.E. . . . . 3s.
- 82\*\*\*. **WATER-WORKS FOR THE SUPPLY OF CITIES AND TOWNS**, by Samuel Hughes, C.E. . . . . 3s.
117. **SUBTERRANEAN SURVEYING, & RANGING THE LINE** without the Magnet, by T. Fenwick, Coal Viewer, with Improvements and Additions by T. Baker, C.E. 2s. 6d.
- 118, 119. **CIVIL ENGINEERING IN NORTH AMERICA**, by D. Stevenson, C.E., 2 vols. in 1 . . . . . 3s.
120. **HYDRAULIC ENGINEERING**, by G. R. Burnell, C.E., 2 vols. in 1 . . . . . 3s.

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.



- 121, 122. RIVERS AND TORRENTS, from the Italian of Paul Frisi, and a Treatise on NAVIGABLE CANALS, AND RIVERS THAT CARRY SAND AND MUD 2s. 6d.  
 125, 126. COMBUSTION OF COAL, AND THE PREVENTION OF SMOKE, by Charles Wye Williams, M.I.C.E. 3s.

## SHIP-BUILDING AND NAVIGATION.

- 51, 52, 53. NAVAL ARCHITECTURE, Principles of the Science, and their Practical Application to Naval Construction, by J. Peake, N.A., 3 vols. in 1 . . . 3s.  
 53\*. SHIPS AND BOATS FOR OCEAN AND RIVER SERVICE, the Principles of Construction, by Captain H. A. Sommerfeldt . . . 1s.  
 53\*\*. ATLAS OF 14 PLATES TO THE PRECEDING, Drawn to a Scale for Practice . . . 7s. 6d.  
 54. MASTING, MAST-MAKING, and RIGGING OF SHIPS, by R. Kipping, N.A. . . . 1s. 6d.  
 54\*. IRON SHIP-BUILDING, by John Grantham, C.E. 2s. 6d.  
 54\*\*. ATLAS OF 24 PLATES TO THE PRECEDING VOLUME . . . 22s. 6d.  
 80, 81. MARINE ENGINES AND THE SCREW, by R. Murray, C.E., 2 vols. in 1 . . . 2s. 6d.  
 83 bis. SHIPS AND BOATS, the Principles of Construction, by W. Bland, of Hartlip . . . 1s.  
 106. SHIPS' ANCHORS FOR ALL SERVICES, by George Cotsett, N.A. . . . 1s. 6d.

## ARITHMETIC AND MATHEMATICS.

32. MATHEMATICAL INSTRUMENTS, AND THEIR USE, by J. F. Heather, M.A. . . . 1s.  
 55, 56. NAVIGATION; the Sailor's Sea Book: How to Keep the Log and Work it off, &c.; Law of Storms, and Explanation of Terms . . . 2s.  
 £1\*. READY RECKONER for the Measurement of Land, its Valuation, and the Price of Labour, by A. Arman, Schoolmaster . . . 1s. 6d.  
 76, 77. GEOMETRY, DESCRIPTIVE, with a Theory of Shadows and Perspective, and a Description of the Principles and Practice of Isometrical Projection, by J. F. Heather, M.A., 2 vols. in 1 . . . 2s.  
 85. EQUATIONAL ARITHMETIC: Questions of Interest, Annuities, &c., by W. Hipsley . . . 1s.

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

- 85\*. **EQUATIONAL ARITHMETIC**: Tables for the Calculation of Simple Interest, with Logarithms for Compound Interest, and Annuities, by W. Hipsley . . . . . 1s.
- 86, 87. **ALGEBRA**, by James Haddon, M.A., 2 vols. in 1 . . . . . 2s.
- 86\*, 87\*. **ELEMENTS OF ALGEBRA**, Key to the, by Prof. Young . . . . . 1s. 6d.
- 88, 89. **GEOMETRY**, Principles of, by Henry Law, C.E., 2 vols. in 1 . . . . . 2s.
90. **GEOMETRY, ANALYTICAL**, by James Hann . . . . . 1s.
- 91, 92. **PLANE AND SPHERICAL TRIGONOMETRY**, by Prof. James Hann, 2 vols. in 1 (*The two divisions separately, 1s. each*) . . . . . 2s.
93. **MENSURATION**, by T. Baker, C.E. . . . . 1s.
- 94, 95. **LOGARITHMS**, Tables of; with Tables of Natural Sines, Co-sines, and Tangents, by H. Law, C.E., 2 vols. in 1 . . . . . 2s. 6d.
97. **STATICS AND DYNAMICS**, by T. Baker, C.E. . . . . 1s.
- 99, 100. **NAVIGATION AND NAUTICAL ASTRONOMY**, by Professor Young, 2 vols. in 1 . . . . . 2s.
- 100\*. **NAVIGATION TABLES**, compiled for Practical Use with the preceding volume . . . . . 1s. 6d.
101. **DIFFERENTIAL CALCULUS**, by Mr. Woolhouse, F.R.A.S. . . . . 1s.
102. **INTEGRAL CALCULUS**, by H. Cox, M.A. . . . . 1s.
104. **DIFFERENTIAL CALCULUS**, Examples of, by J. Haddon, M.A. . . . . 1s.
105. **ALGEBRA, GEOMETRY, AND TRIGONOMETRY**, First Mnemonical Lessons in, by the Rev. T. P. Kirkman, M.A. . . . . 1s. 6d.

## MISCELLANEOUS.

50. **LAW OF CONTRACTS FOR WORKS AND SERVICES**, by David Gibbons, S.P. . . . . 1s.
107. **METROPOLITAN BUILDINGS ACT**, and **THE METROPOLITAN ACT FOR REGULATING THE SUPPLY OF GAS**, with Notes . . . . . 2s. 6d.
108. **METROPOLITAN LOCAL MANAGEMENT ACTS**, 1s. 6d.
110. **RECENT LEGISLATIVE ACTS** applying to Contractors, Merchants, and Tradesmen . . . . . 1s.
111. **NUISANCES REMOVAL AND DISEASE PREVENTION ACT** . . . . . 1s.
113. **USE OF FIELD ARTILLERY ON SERVICE**, by Lieut.-Colonel Hamilton Maxwell, B.A. . . . . 1s. 6d.
- 113\*. **MEMOIR ON SWORDS**, by the same . . . . . 1s.
- 83\*\*. **CONSTRUCTION OF DOOR LOCKS** . . . . . 1s. 6d.

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

# NEW SERIES OF EDUCATIONAL WORKS.

[This Series is kept in three styles of binding—the prices of each are given in columns at the end of the lines.]

HISTORIES, GRAMMARS, AND DICTIONARIES.	Limp.	Cloth Boards.	Half Morocco.
	s. d.	s. d.	s. d.
1, 2, 3, 4. CONSTITUTIONAL HISTORY OF England, by W. D. Hamilton . . . . .	4 0	5 0	5 6
5, 6. OUTLINES OF THE HISTORY OF Greece, by E. Leven, M.A., 2 vols. in 1 . . . . .	2 6	3 6	4 0
7, 8. OUTLINES OF THE HISTORY OF Rome, by the same, 2 vols. in 1 . . . . .	2 6	3 6	4 0
9, 10. CHRONOLOGY OF CIVIL AND Ecclesiastical History, Literature, Art, and Civilization, from the earliest period to the present, 2 vols. in 1 . . . . .	2 6	3 6	4 0
11. GRAMMAR OF THE ENGLISH LANGUAGE, by Hyde Clarke, D.C.L. . . . .	1 0		
11*. HAND-BOOK OF COMPARATIVE Philology, by the same . . . . .	1 0		
12, 13. DICTIONARY OF THE ENGLISH Language.—A new Dictionary of the English Tongue, as spoken and written; above 100,000 words, or 50,000 more than in any existing work, by the same, 3 vols. in 1 . . . . .	3 6	4 6 5 6	5 0 6 0
14. GRAMMAR OF THE GREEK LANGUAGE, by H. C. Hamilton . . . . .	1 0		
15, 16. DICTIONARY OF THE GREEK AND English Languages, by H. R. Hamilton, 2 vols. in 1 . . . . .	2 0		
17, 18. DICTIONARY OF THE ENGLISH and Greek Languages, by the same, 2 vols. in 1 . . . . .	2 0		
_____ GREEK AND ENGLISH and English and Greek, 4 vols. in 1 . . . . .		5 0 6 0	5 6 6 6
_____ with the Greek Grammar . . . . .			
19. GRAMMAR OF THE LATIN LANGUAGE, by the Rev. T. Goodwin, A.B. . . . .	1 0		
20, 21. DICTIONARY OF THE LATIN AND English Languages, by the same. Vol. I. . . . .	2 0		
22, 23. DICTIONARY OF THE ENGLISH and Latin Languages, by the same. Vol. II. . . . .	1 6		
_____ 2 vols. in 1 . . . . .		4 6 5 6	5 0 6 0
_____ with the Latin Grammar . . . . .			
24. GRAMMAR OF THE FRENCH LANGUAGE, by the Lecturer at Besançon . . . . .	1 0		

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

HISTORIES, GRAMMARS, AND DICTIONARIES.	Limp.	Cloth Boards.	Half Morocco.
	s. d.	s. d.	s. d.
25. DICTIONARY OF THE FRENCH AND English Languages, by A. Elwes. Vol. I.	1 0		
26. DICTIONARY OF THE ENGLISH AND French Languages, by the same. Vol. II.	1 6		
—, 2 vols. in 1 . . . . .		3 6	4 0
—, with the French Grammar . . . . .		4 6	5 0
27. GRAMMAR OF THE ITALIAN LANGUAGE, by the same . . . . .	1 0		
28, 29. DICTIONARY OF THE ITALIAN, English, and French Languages, by the same. Vol. I. . . . .	2 0		
30, 31. DICTIONARY OF THE ENGLISH, Italian, and French Languages, by the same. Vol. II. . . . .	2 0		
32, 33. DICTIONARY OF THE FRENCH, Italian, and English Languages, by the same. Vol. III. . . . .	2 0		
—, 3 vols. in 1 . . . . .		7 6	8 6
—, with the Italian Grammar . . . . .		8 6	9 6
34. GRAMMAR OF THE SPANISH LANGUAGE, by the same . . . . .	1 0		
35, 36, 37, 38. DICTIONARY OF THE Spanish and English Languages, by the same, 4 vols. in 1 . . . . .	4 0	5 0	5 6
—, with the Spanish Grammar . . . . .		6 0	6 6
39. GRAMMAR OF THE GERMAN LANGUAGE, by the Lecturer at Besançon . . . . .	1 0		
40. CLASSICAL GERMAN READER, from the best authors, by the same . . . . .	1 0		
41, 42, 43. DICTIONARIES OF THE ENGLISH, German, and French Languages, by N. E. Hamilton, 3 vols., separately 1s. each . . . . .	3 0	4 0	4 6
—, with the German Grammar . . . . .		5 0	5 6
44, 45. DICTIONARY OF THE HEBREW and English Languages, containing the Biblical and Rabbinical words, 2 vols. (together with the Grammar, which may be had separately for 1s.) by Dr. BRESSLAU, Hebrew Professor . . . . .	7 0		
46. DICTIONARY OF THE ENGLISH AND Hebrew Languages. Vol. III. to complete, by the same . . . . .	3 0		
—, 3 vols. as 2 . . . . .		12 0	14 0
47. FRENCH AND ENGLISH PHRASE Book . . . . .	1 0	1 6	

*Now in the course of Publication.*

## GREEK AND LATIN CLASSICS.

A Series of Volumes containing the principal Greek and Latin Authors, accompanied by Explanatory Notes in English, principally selected from the best and most recent German Commentators, and comprising all those Works that are essential for the Scholar and the Pupil, and applicable for the Universities of Oxford, Cambridge, Edinburgh, Glasgow, Aberdeen, and Dublin; the Colleges at Belfast, Cork, Galway, Winchester, and Eton; and the great Schools at Harrow, Rugby, &c.—also for Private Tuition and Instruction, and for the Library.

### LATIN SERIES.

1. A New LATIN DELECTUS, Extracts from Classical Authors, with Vocabularies and Explanatory Notes . . . 1s.
2. CÆSAR'S COMMENTARIES on the GALLIC WAR; with Grammatical and Explanatory Notes in English, and a Geographical Index . . . 2s.
3. CORNELIUS NEPOS; with English Notes, &c. . . 1s.
4. VIRGIL. The Georgics, Bucolics; and doubtful Works; with English Notes . . . 1s.
5. VIRGIL'S ÆNEID (on the same plan as the preceding) . . 2s.
6. HORACE. Odes and Epodes; with English Notes, and Analysis and Explanation of the Metres . . . 1s.
7. HORACE. Satires and Epistles; with English Notes, &c. 1s. 6d.
8. SALLUST. Conspiracy of Catiline, Jugurthine War . . 1s. 6d.
9. TERENCE. Andria and Heautontimorumenos . . . 1s. 6d.
10. TERENCE. Phormio, Adelphi, and Hecyra . . . 2s.
14. CICERO. De Amicitia, de Senectute, and Brutus . . . 2s.
16. LIVY. Books i. to v. in two parts . . . 3s.
17. LIVY. Books xxi. and xxii. . . . 1s.
19. Selections from TIBULLUS, OVID, and PROPERTIUS . . 2s.
20. Selections from SÜETONIUS and the later Latin Writers . 2s.

#### *Preparing for Press.*

11. CICERO. Orations against Catiline, for Sulla, for Archias, and for the Manilian Law.
12. CICERO. First and Second Philippics; Orations for Milo, for Marcellus, &c.
13. CICERO. De Officiis.
15. JUVENAL and PERSIUS. (The indelicate passages expunged.)
18. TACITUS. Agricola; Germania; and Annals, Book i.

---

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.

## GREEK SERIES,

ON A SIMILAR PLAN TO THE LATIN SERIES.

1. **INTRODUCTORY GREEK READER.** On the same plan as the Latin Reader . . . . . 1s.
2. **XENOPHON.** *Anabasis*, i. ii. iii. . . . . 1s.
3. **XENOPHON.** *Anabasis*, iv. v. vi. vii. . . . . 1s.
4. **LUCIAN.** *Select Dialogues* . . . . . 1s.
5. **HOMER.** *Iliad*, i. to vi. . . . . 1s. 6d.
6. **HOMER.** *Iliad*, vii. to xii. . . . . 1s. 6d.
7. **HOMER.** *Iliad*, xiii. to xviii. . . . . 1s. 6d.
8. **HOMER.** *Iliad*, xix. to xxiv. . . . . 1s. 6d.
9. **HOMER.** *Odyssey*, i. to vi. . . . . 1s. 6d.
10. **HOMER.** *Odyssey*, vii. to xii. . . . . 1s. 6d.
11. **HOMER.** *Odyssey*, xiii. to xviii. . . . . 1s. 6d.
12. **HOMER.** *Odyssey*, xix. to xxiv.; and *Hymns* . . . . . 2s.
13. **PLATO.** *Apology*, *Crito*, and *Phædo* . . . . . 2s.
14. **HERODOTUS**, i. ii. . . . . 1s. 6d.
15. **HERODOTUS**, iii. iv. . . . . 1s. 6d.
16. **HERODOTUS**, v. vi. and part of vii. . . . . 1s. 6d.
17. **HERODOTUS.** *Remainder of vii. viii. and ix.* . . . . 1s. 6d.
18. **SOPHOCLES;** *Cedipus Rex* . . . . . 1s.
23. **EURIPIDES;** *Hecuba* } . . . . . 1s. 6d.
24. **EURIPIDES;** *Medea* }
- Nos. 23 and 24 separately, 1s. each.
26. **EURIPIDES;** *Alcesteis* . . . . . 1s.
41. **THUCYDIDES**, i. . . . . 1s.

*Preparing for Press.*

19. **SOPHOCLES;** *Cedipus Colonusæus*.
20. **SOPHOCLES;** *Antigone*.
21. **SOPHOCLES;** *Ajax*.
22. **SOPHOCLES;** *Philoctetes*.
25. **EURIPIDES;** *Hippolytus*.
27. **EURIPIDES;** *Orestes*.
28. **EURIPIDES.** *Extracts from the remaining plays.*
29. **SOPHOCLES.** *Extracts from the remaining plays.*
30. **ÆSCHYLUS;** *Prometheus Vincetus*.
31. **ÆSCHYLUS;** *Persæ*.
32. **ÆSCHYLUS;** *Septem contra Thebes*.
33. **ÆSCHYLUS;** *Choëphoræ*.
34. **ÆSCHYLUS;** *Eumenides*.
35. **ÆSCHYLUS;** *Agamemnon*.
36. **ÆSCHYLUS;** *Supplices*.
37. **PLUTARCH;** *Select Lives*.
38. **ARISTOPHANES;** *Clouds*.
39. **ARISTOPHANES;** *Frogs*.
40. **ARISTOPHANES;** *Selections from the remaining Comedies.*
42. **THUCYDIDES**, ii.
43. **THEOCRITUS;** *Select Idyls*.
44. **PINDAR.**
45. **ISOCRATES.**
46. **HESIOD.**

In 2 vols. super-royal 8vo., price £2 5s., cloth gilt,  
**TOMLINSON'S CYCLOPÆDIA OF USEFUL ARTS**, Mechanical and Chemical, Manufactures, Mining, and Engineering; with 40 Engravings on Steel, and 2,477 Woodcuts.

In 3 vols. royal 4to., price £4 14s. 6d.,  
**TREDGOLD ON THE STEAM ENGINE**; Its Principles, Practice, and Construction. Illustrated by upwards of 200 Engravings, and 160 Woodcuts and Diagrams.

In 1 vol. demy 4to., price £1 11s. 6d.,  
**NICHOLSON'S CARPENTER'S GUIDE**. Edited by JOHN HAY, Esq., Architect, Liverpool. Illustrated by numerous Engravings.

In 1 vol. post 8vo., price 10s. 6d., cloth,  
**A DICTIONARY OF TERMS IN ART**; Edited and illustrated by F. W. FAIRHOLT, F.S.A., Author of "Costume in England," &c.; Honorary Member of the Society of Antiquaries of Normandy, Poitiers, and Picardy; and Corresponding Member of the Society of Antiquaries of Scotland. Illustrated by 500 Engravings.

In demy 4to., price 12s., cloth lettered,  
**PRACTICAL HINTS ON PORTRAIT PAINTING**: Illustrated by Examples from the Works of Vandyke and other Artists. By JOHN BURNET, F.R.S., Author of "Letters on Landscape Painting," "Rembrandt and his Works," &c. &c. With 12 Engravings on Steel. Re-edited, and with an Appendix, by HENRY MURRAY, F.S.A.

In demy 4to., price 12s., cloth lettered,  
**LANDSCAPE PAINTING IN OIL COLOURS**, Explained in Letters on the Theory and Practice of the Art, and illustrated by Examples from the several Schools. By JOHN BURNET, F.R.S., Author of "Practical Hints on Painting," "Rembrandt and his Works," &c. &c. Re-edited, with an Appendix, by HENRY MURRAY, F.S.A. Illustrated with 11 Steel Engravings.

In 1 vol. demy 8vo., price 5s.,  
**THE SCHOOL PERSPECTIVE**: Being a Progressive Course of Instruction in Linear Perspective, both Theoretical and Practical. Specially designed for the Use of Schools. By J. R. DICKSEE, Principal Drawing Master to the City of London School; to the Normal College for Training Teachers of the British and Foreign School Society. Illustrated with many Woodcuts and 40 Engraved Plates.

JAMES S. VIRTUE, 294, CITY ROAD, AND 26, IVY LANE.











**FA1567.3**

The art of architectural modelling  
Fine Arts Library

BA11272



3 2044 034 390 674

**This book should be returned to  
the Library on or before the last date  
stamped below.**

**A fine of five cents a day is incurred  
by retaining it beyond the specified  
time.**

**Please return promptly.**

